

Instruction Manual for N200 to N120 Port Adaptor for Epic/Weapon LT Housings

PN# 16420

FOREWORD

Thank you for your purchase of a NAUTICAM product.

At NAUTICAM, we pride ourselves in the ability to recognize the requirements of professional as well as amateur underwater photographers and fulfill them through the innovative designs of our products. We strive to achieve a high level of user-friendliness by allowing stress-free installation and easy operation of all important functions of the camera.

Please read this manual carefully before using the product, this will maximize its performance as well as its lifetime.

WARRANTY

All NAUTICAM Products are warranted against any material and manufacturing defects for two years from the date of purchase for consumer use. This warranty only applies to products purchased from authorized NAUTICAM dealers and does not extend beyond the original retail purchaser.

To return your product for service, please contact your regional authorized service center(s). Please note that this warranty only applies when the product is purchased in the territory where the service center is located.

NAUTICAM does not hold responsibility for damage, of any nature, to any equipment used with and/or placed within our products.

NAUTICAM accepts no liability for any loss of captured images or the inability to capture images even if it is due to the malfunctioning of our products.

Unauthorized modifications and/or repairs of our products will automatically invalidate the warranty.

PACKAGE CONTENTS

- N200 to N120 Port Adaptor for Epic/Weapon LT Housings
- Cloth Bag
- 90122 Silicone Rubber O-ring
- Lubricant
- Manual Instruction Card





Housing alignment dot

CONNECT WITH PORT



1. Confirm that the port adaptor is unlocked, with the locking lever pointing upwards as shown.



2. Align the "I" mark on the port adaptor with the white dot on the port. Then, gently push the port to the port adaptor until it cannot go in any further.



3. Turn the port adaptor clockwise until the white dot on the port adaptor aligns with the white dot on the port.



4. Lock the port by turning the locking lever to the 'lock' position as shown.

SPECIFICATIONS	
Dimensions(mm):	DIA219.7×33.0
Depth rating:	70m
Body construction	Hard-anodized aluminum alloy

Remark: Nauticam supports only e-manuals. Please download corresponding product manuals on <u>Nauticam.com</u> website, or contact us for e-manuals.