



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	PORT BASE	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO APS-C	Canon EF-S 60mm f2.8 Macro USM	19521 C60-F	18211 Compact Port Base		18704 Macro Port 41	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81302 CMC - 2	Max. Magnification 1.6X Working Distance 38-120mm
							81201 SMC - 1	Max. Magnification 1.6X Working Distance 28-94mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2	Max. Magnification 1.6X Working Distance 38-120mm
							81201 SMC - 1	Max. Magnification 1.6X Working Distance 28-94mm
					18303 Compact Port 15	83250 M67 to Bayonet Mount Converter II	87302 EMWL Set #2	Lens FOV 24.5° Converted FOV 60°/100°/130°/160°
MACRO FULL FRAME	Laowa 24mm f/14 2X Macro Probe	19155 N120 DSLR Gear Set		22170 + 22171 N120 Extension Ring 70 II + Focus Knob	16336 N120 Port Adaptor for Laowa 24mm f/14 2X			
	Canon EF 40mm f2.8 STM <i>* This setup can only be used on APS-C sensor camera</i>				18706 Macro Port 12	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	On APS-C Sensor Lens FOV 37° Converted FOV 135°
	Canon MP-E 65mm f/2.8 1-5x	19539 C65-F	18211 Compact Port Base	18550 Compact Port Extension 50	18306 Compact Port 50 with M67 Thread <i>* magnification 3X</i>			
				18550 + 18530 Compact Port Extension 50 + 30	18306 Compact Port 50 with M67 Thread <i>* magnification 4X</i>			
			18550 + 18530 + 18530 Compact Port Extension 50 + 30 + 30	18306 Compact Port 50 with M67 Thread <i>* magnification 5X</i>				
Canon EF 100mm f2.8 Macro USM	19522 C100-F				18702 Macro Port 87	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 2.6X Working Distance 53-93mm
							81202 SMC - 2	Max. Magnification 4.3X Working Distance 28-38mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 2.6X Working Distance 53-93mm
							81202 SMC - 2	Max. Magnification 4.3X Working Distance 28-38mm
					83250 M67 to Bayonet Mount Converter II	87301 EMWL Set #1	Lens FOV 24° Converted FOV 60°/100°/130°/160°	
Canon EF 100mm f/2.8L Macro IS USM	19523 C100IS-F				18703 Macro Port 94	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 2.2X Working Distance 45-89mm
							81202 SMC - 2	Max. Magnification 3.6X Working Distance 22-36mm

** Please refer to the following page for more setup options*

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

** Recommended port system based on best optical performance
* Secondary setup recommendation based on optical performance*



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO FULL FRAME	Canon EF 100mm f/2.8L Macro IS USM	19523 C100IS-F			18703 Macro Port 94	SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 2.2X Working Distance 45-89mm
							81202 SMC - 2	Max. Magnification 3.6X Working Distance 22-36mm
						83250 M67 to Bayonet Mount Converter II	87302 EMWL Set #2	Lens FOV 23.4° Converted FOV 60°/100°/130°/160°
	Canon EF 180mm f/3.5L Macro USM			22160 N120 Extension Ring 60 II	18703 Macro Port 94	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 3.6X Working Distance 63-92mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 3.6X Working Distance 63-92mm
	Sigma 50mm F2.8 EX DG Macro			18211 Compact Port Base	18520 Compact Port Extension 20	18303 Compact Port 15		
	Sigma 70mm F2.8 EX DG Macro			18211 Compact Port Base	18530 Compact Port Extension 30	18302 Compact Port 50		
							18211 Compact Port Base	18550 Compact Port Extension 50
	Sigma 105mm F2.8 EX DG OS HSM Macro	19553 SC105-F		22130 N120 Extension Ring 30 II	18701 Macro Port 60	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 2.6X Working Distance 50-90mm
						81202 SMC - 2	Max. Magnification 3.3X Working Distance 31-38mm	
SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC						81201 SMC - 1	Max. Magnification 2.6X Working Distance 50-90mm	
						81202 SMC - 2	Max. Magnification 3.3X Working Distance 31-38mm	
83250 M67 to Bayonet Mount Converter II						87301 EMWL Set #1	Lens FOV 24° Converted FOV 60°/100°/130°/160°	
STANDARD ZOOM APS-C	Canon EF-S 18-55mm f/3.5-5.6 IS	19532 C1855IS-Z	18211 Compact Port Base		18303 Compact Port 15			
	Canon EF-S 18-55mm f/3.5-5.6 IS STM	19547 C1855ISSTM-Z	18211 Compact Port Base		18303 Compact Port 15			
				22130 N120 Extension Ring 30 II		85201 N120 WACP - 1	Lens FOV 75-27.5° Converted FOV 130-46°	
			21325 N120 to N100 25mm Port Adaptor		85205 N100 WACP - C	Lens FOV 75-27.5° Converted FOV 130-46°		
	Canon EF-S 18-135mm f/3.5-5.6 IS	19524 C18135IS-Z		22160 N120 Extension Ring 60 II		18802 8.5" Acrylic Dome Port		
	Sigma 17-70mm F2.8-4.5 DC Macro	19533 SC1770-Z		22150 N120 Extension Ring 50 II		18802 8.5" Acrylic Dome Port		
Sigma 17-70mm F2.8-4 DC Macro OS HSM	19534 SC17700S-Z		22140 N120 Extension Ring 40 II		18802 8.5" Acrylic Dome Port			

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance
* Secondary setup recommendation based on optical performance



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING/ PORT ADAPTOR	PORT	OPTICAL PERFORMANCE
STANDARD ZOOM APSC	Sigma 18-35mm F1.8 DC HSM A	19552 SC1835f.18-Z		22180 N120 Extension Ring 80 II	* 85202 N120 WACP-1 for Sigma 18-35mm F1.8	Lens FOV 76.5-44° Converted FOV 132-76°
					18802 8.5" Acrylic Dome Port	
					* 18809 180mm Optical Glass Wide Angle Port	
					18812 230mm Optical Glass Wide Angle Port II	
					22130 + 22135 N120 Extension Ring 30 II + 35 II	85201 N120 WACP - 1
22140 + 21325 N120 Extension Ring 40 II + N120 to N100 25mm Port Adaptor	85205 N100 WACP - C	Lens FOV 76.5-44° Converted FOV 132-76°				
22150 + 22150 N120 Extension Ring 50 II + 50 II	18815 250mm Optical Glass Wide Angle Port II					
STANDARD ZOOM FULL FRAME	Canon EF 24mm f/1.4L II USM			22140 N120 Extension Ring 40 II	18802 8.5" Acrylic Dome Port	
	Canon EF 24-70mm f/2.8L II USM	19543 C2470II-Z		22170 N120 Extension Ring 70 II	18802 8.5" Acrylic Dome Port	
	Canon EF 24-70mm f/4L IS USM	19544 C2470f4-Z		22170 N120 Extension Ring 70 II	18802 8.5" Acrylic Dome Port	
	Canon EF 24-105mm f/4L IS USM	19545 C24105-Z		22170 N120 Extension Ring 70 II	18802 8.5" Acrylic Dome Port	
	Canon EF 24-105mm f/4L IS II USM	19562 C24105II-Z		22170 N120 Extension Ring 70 II	18802 8.5" Acrylic Dome Port	
				22190 N120 Extension Ring 90 II	* 18809 180mm Optical Glass Wide Angle Port	
					18812 230mm Optical Glass Wide Angle Port II	
					18815 250mm Optical Glass Wide Angle Port II	
	Canon EF 28mm f/1.8 USM				85201 N120 WACP - 1	Lens FOV 75° Converted FOV 130°
	Canon EF 28mm f/2.8 USM				85201 N120 WACP - 1	Lens FOV 75° Converted FOV 130°
Canon EF 28-70mm f/3.5-4.5 II	19557 C2870f3.5II-Z		22125 N120 Extension Ring 25 II	* 85201 N120 WACP - 1	Lens FOV 72-34° Converted FOV 130-59°	
		21325 N120 to N100 25mm Port Adaptor		85205 N100 WACP - C	Lens FOV 72-34° Converted FOV 130-59°	

* Please refer to the following page
for more setup options

* slight vignetting when focus distance from port to subject is less than 10cm at 28mm



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
STANDARD ZOOM FULL FRAME	Canon EF 28-70mm f/3.5-4.5 II	19557 + 19566 C2870f3.5II-Z + C2870f3.5II-F		22130 + 22131 N120 Extension Ring 30 II + Focus Knob	85201 N120 WACP - 1			Lens FOV 72-34° Converted FOV 125-59° Zoom Range 30-70mm
	Canon EF 28-80mm f/3.5-5.6 II	19558 C2880f3.5II-Z		22120 N120 Extension Ring 20 II	18705 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 36-30° Converted FOV 135-113° Zoom Range 66-80mm
				22130 N120 Extension Ring 30 II	85201 N120 WACP - 1		Lens FOV 75-30° Converted FOV 130-54°	
				21325 N120 to N100 25mm Port Adaptor	85205 N100 WACP - C		Lens FOV 75-30° Converted FOV 130-54° <i>* slight vignetting when focus distance from port to subject is less than 10cm at 28mm</i>	
Canon EF 28-80mm f/3.5-5.6 V USM	19559 C2880f3.5V-Z		22120 N120 Extension Ring 20 II	18705 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 37.5-30° Converted FOV 138-93° Zoom Range 63-80mm	
			22130 N120 Extension Ring 30 II	85201 N120 WACP - 1		Lens FOV 75-31° Converted FOV 130-54°		
			21325 N120 to N100 25mm Port Adaptor	85205 N100 WACP - C		Lens FOV 75-31° Converted FOV 130-54°		
Canon EF 35mm f/2 IS USM				85201 N120 WACP - 1			Lens FOV 63° Converted FOV 109°	
WIDE ANGLE APSC	Canon EF-S 10-18mm f/4.5-5.6 IS STM	19549 C1018-Z		22140 N120 Extension Ring 40 II	18809 180mm Optical Glass Wide Angle Port			Lens FOV 108-75° Converted FOV 128-85°
				22150 N120 Extension Ring 50 II	18802 8.5" Acrylic Dome Port			
					18809 180mm Optical Glass Wide Angle Port			
	Canon EF-S 10-22mm f/3.5-4.5 IS STM	19525 C1022-Z		21110 N120 Extension Ring 10	85204 N120 WACP - 2			Lens FOV 108-63° Converted FOV 128-72° <i>* This setup is only compatible with WACP-2 before SN:A526311</i>
				22110 N120 Extension Ring 10 II	85204 N120 WACP - 2			Lens FOV 108-63° Converted FOV 128-72° <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>
				22150 N120 Extension Ring 50 II	18809 180mm Optical Glass Wide Angle Port			
				22160 N120 Extension Ring 60 II	18802 8.5" Acrylic Dome Port			
					18809 180mm Optical Glass Wide Angle Port			
	* 18812 230mm Optical Glass Wide Angle Port II							

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance
* Secondary setup recommendation based on optical performance



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE	
WIDE ANGLE APS-C	Sigma 8-16mm F4.5-5.6 DC HSM	19536 SC816-Z	22140 N120 Extension Ring 40 II	18809 180mm Optical Glass Wide Angle Port		
			22150 N120 Extension Ring 50 II	18802 8.5" Acrylic Dome Port		
				18812 230mm Optical Glass Wide Angle Port II		
				* 18815 250mm Optical Glass Wide Angle Port II		
	Sigma 10-20mm F4.5-5.6 EX DC HSM	19535 SC1020-Z	22140 N120 Extension Ring 40 II	18809 180mm Optical Glass Wide Angle Port		
			22150 N120 Extension Ring 50 II	18802 8.5" Acrylic Dome Port		
				18812 230mm Optical Glass Wide Angle Port II		
				* 18815 250mm Optical Glass Wide Angle Port II		
	Tokina AT-X 11-20mm F2.8 PRO DX	19573 CT1120-Z	22120 N120 Extension Ring 20 II	85204 N120 WACP - 2	Lens FOV Converted FOV	104-72° 118-78°
			22160 N120 Extension Ring 60 II	18802 8.5" Acrylic Dome Port		
				18809 180mm Optical Glass Wide Angle Port		
				18812 230mm Optical Glass Wide Angle Port II		
			* 18815 250mm Optical Glass Wide Angle Port II			
Tokina AT-X 116 PRO DX AF 11-16mm f/2.8	19530 TC1116-Z	21110 N120 Extension Ring 10	85204 N120 WACP - 2	Lens FOV Converted FOV	110-81° 133-92°	
		22110 N120 Extension Ring 10 II	85204 N120 WACP - 2	Lens FOV Converted FOV	110-81° 133-92°	
		22160 N120 Extension Ring 60 II	18802 8.5" Acrylic Dome Port			
			18809 180mm Optical Glass Wide Angle Port			
			18812 230mm Optical Glass Wide Angle Port II			
			* 18815 250mm Optical Glass Wide Angle Port II			
Tokina AT-X 124 AF PRO DX AF 12-24mm f/4	19531 TC1224-Z	22150 N120 Extension Ring 50 II	18802 8.5" Acrylic Dome Port			
		22160 N120 Extension Ring 60 II	18809 180mm Optical Glass Wide Angle Port			

*Please refer to the following page for more setup options



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE	
WIDE ANGLE APS-C	Tokina AT-X 124 AF PRO DX AF 12-24mm f/4	19531 TC1224-Z	22160 N120 Extension Ring 60 II	18812 230mm Optical Glass Wide Angle Port II		
				* 18815 250mm Optical Glass Wide Angle Port II		
WIDE ANGLE FULL FRAME	Canon EF 11-24mm f/4L USM	19550 C1124-Z	22150 N120 Extension Ring 50 II	* 18815 250mm Optical Glass Wide Angle Port II	* This setup is not compatible with Extension Rings I SN:A213191 before 09/2016	
				22170 N120 Extension Ring 70 II	18812 230mm Optical Glass Wide Angle Port II	* This setup is not compatible with Extension Rings I SN:A201966 before 09/2016
					22170 + 22171 N120 Extension Ring 70 II + Focus Knob	18812 230mm Optical Glass Wide Angle Port II
	Canon EF 16-35mm f/2.8 II USM	19527 C1635II-Z	22130 N120 Extension Ring 30 II	* 85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°	
				22170 N120 Extension Ring 70 II	18802 8.5" Acrylic Dome Port	
					18809 180mm Optical Glass Wide Angle Port	
			22180 N120 Extension Ring 80 II	18812 230mm Optical Glass Wide Angle Port II		
				* 18815 250mm Optical Glass Wide Angle Port II		
				22130 + 22131 N120 Extension Ring 30 II + Focus Knob	85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°
	Canon EF 16-35mm f/2.8 III USM	19554 C1635III-Z	22150 N120 Extension Ring 50 II	* 85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°	
				22170 N120 Extension Ring 70 II	85201 N120 WACP - 1	On APS-C Sensor Lens FOV 80-43° Converted FOV 138-74°
			22180 N120 Extension Ring 80 II		18809 180mm Optical Glass Wide Angle Port	On Full Frame Sensor Lens FOV 75-63° Converted FOV 130-109° Zoom Range 28-35mm
19554 + 19555 C1635III-Z + C1635III-F	22150 + 22151 N120 Extension Ring 50 II + Focus Knob	85204 N120 WACP - 2		Lens FOV 107-63° Converted FOV 128-72°		
			22170 + 22171 + 22120 N120 Extension Ring 70 II + Focus knob + 20 II	* 18812 230mm Optical Glass Wide Angle Port II		

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance
* Secondary setup recommendation based on optical performance



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE
WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/4 IS USM	19548 C1635f4-Z	22130 N120 Extension Ring 30 II	* 85204 N120 WACP - 2	Lens FOV 108-63° Converted FOV 128-72°
			22160 N120 Extension Ring 60 II	85201 N120 WACP - 1 On APS-C Sensor	Lens FOV 80-43° Converted FOV 138-74°
			22170 N120 Extension Ring 70 II	18802 8.5" Acrylic Dome Port 18809 180mm Optical Glass Wide Angle Port	
		22180 N120 Extension Ring 80 II	* 18812 230mm Optical Glass Wide Angle Port II 18815 250mm Optical Glass Wide Angle Port II		
		19548 + 19560 C1635f4-Z + C1635f4-F	22170 + 22171 N120 Extension Ring 70 II + Focus Knob	18812 230mm Optical Glass Wide Angle Port II	
		19548 + 19572 C1635f4-Z + WC1635f4-F	22135 + 22151 N120 Extension Ring 35 II + Focus Knob	85204 N120 WACP - 2	Lens FOV 108-63° Converted FOV 128-72°
	Canon EF 17-40mm f/4L USM	19528 C1740-Z	22140 N120 Extension Ring 40 II	85201 N120 WACP - 1 On APS-C Sensor	Lens FOV 77-37° Converted FOV 133-74°
			22150 N120 Extension Ring 50 II	18802 8.5" Acrylic Dome Port	
			22160 N120 Extension Ring 60 II	18809 180mm Optical Glass Wide Angle Port	
			22170 N120 Extension Ring 70 II	18812 230mm Optical Glass Wide Angle Port II * 18815 250mm Optical Glass Wide Angle Port II	
			22150 N120 Extension Ring 50 II	18815 250mm Optical Glass Wide Angle Port II On Full Frame Sensor	Lens FOV 75-57.5° Converted FOV 130-100°
			22160 N120 Extension Ring 60 II	18802 8.5" Acrylic Dome Port	
Sigma 12-24mm F4 DG HSM Art	19556 SC1224A-Z	22150 N120 Extension Ring 50 II	18815 250mm Optical Glass Wide Angle Port II	* This setup is not compatible with Extension Rings I SN:A213191 before 09/2016	
		22160 N120 Extension Ring 60 II	* 18812 230mm Optical Glass Wide Angle Port II	* This setup is not compatible with Extension Rings I SN:A143566 before 09/2016	
Sigma 14mm F1.8 DG HSM Art	19563 SC14A-F	22170 N120 Extension Ring 70 II	18802 8.5" Acrylic Dome Port * 18812 230mm Optical Glass Wide Angle Port II	* This setup is not compatible with Extension Rings I SN:A201966 before 09/2016	
		22160 N120 Extension Ring 60 II	18809 180mm Optical Glass Wide Angle Port	* This setup is not compatible with Extension Rings I SN:A143566 before 09/2016	
Sigma 14-24mm F2.8 DG HSM Art	19564 SC1424A-Z	22160 N120 Extension Ring 60 II	18809 180mm Optical Glass Wide Angle Port	* This setup is not compatible with Extension Rings I SN:A143566 before 09/2016	
		22170 N120 Extension Ring 70 II	18802 8.5" Acrylic Dome Port * 18812 230mm Optical Glass Wide Angle Port II	* This setup is not compatible with Extension Rings I SN:A201966 before 09/2016	

* Please refer to the following page
for more setup options



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	
WIDE ANGLE FULL FRAME	Sigma 14-24mm F2.8 DG HSM Art	19564 SC1424A-Z	22170 N120 Extension Ring 70 II	18815 250mm Optical Glass Wide Angle Port II	
	Sigma 20mm F1.4 DG HSM A		22160 N120 Extension Ring 60 II	18809 180mm Optical Glass Wide Angle Port	
			22170 N120 Extension Ring 70 II	18802 8.5" Acrylic Dome Port	
				* 18812 230mm Optical Glass Wide Angle Port II	
				18815 250mm Optical Glass Wide Angle Port II	
	ZEISS Distagon T* 15mm f/2.8 ZM	16319 ZC15-F	22155 N120 Extension Ring 55 II	18812 230mm Optical Glass Wide Angle Port II	<i>* This setup is not compatible with Extension Rings I SN:A055053 before 09/2016</i>
	ZEISS Milvus 18mm f/2.8 ZE	16329 ZMC-F	22155 N120 Extension Ring 55 II	18809 180mm Optical Glass Wide Angle Port	
				* 18812 230mm Optical Glass Wide Angle Port II	
	ZEISS Milvus 21mm f/2.8 ZE	16329 ZMC-F	22150 N120 Extension Ring 50 II	18809 180mm Optical Glass Wide Angle Port	
				* 18812 230mm Optical Glass Wide Angle Port II	
FISHEYE APS-C	Sigma 10mm F2.8 EX DC HSM Fisheye			18802 8.5" Acrylic Dome Port	
	Tokina AT-X 107 AF DX Fisheye AF 10-17mm f/3.5-4.5	19529 TC1017-Z		18804 4.33" Acrylic Dome Port for Tokina 10-17mm	
			21110 N120 Extension Ring 10	* 18810 140mm Optical Glass Fisheye Port	<i>* This setup is only compatible with 18810 before SN:A490446</i>
			22110 N120 Extension Ring 10 II	* 18810 140mm Optical Glass Fisheye Port	<i>This setup is only compatible with 18810 SN:A490446 onwards</i>
			22120 N120 Extension Ring 20 II	18802 8.5" Acrylic Dome Port	
				18812 230mm Optical Glass Wide Angle Port II	
	Tokina AT-X 107 AF DX Fisheye AF 10-17mm f/3.5-4.5 with Kenko TELEPLUS HD pro 1.4x DGX Teleconverter for Canon EF	19629 TC1017-Z + 1.4X	22120 N120 Extension Ring 20 II	18804 4.33" Acrylic Dome Port for Tokina 10-17mm	
			22130 N120 Extension Ring 30 II	* 18810 140mm Optical Glass Fisheye Port	
			22140 N120 Extension Ring 40 II	18802 8.5" Acrylic Dome Port	
				18812 230mm Optical Glass Wide Angle Port II	

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

** Recommended port system based on best optical performance*
** Secondary setup recommendation based on optical performance*



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT
FISHEYE FULL FRAME	Canon EF 8-15mm f/4L Fisheye USM	19537 C815-Z	22130 N120 Extension Ring 30 II	18802 8.5" Acrylic Dome Port * 18811 140mm Optical Glass Fisheye Port with Removable Shade 18812 230mm Optical Glass Wide Angle Port II
		19537 + 19541 C815-Z + C815-F	22130 + 22131 N120 Extension Ring 30 II + Focus Knob	18802 8.5" Acrylic Dome Port
	Canon EF 8-15mm f/4L Fisheye USM with Kenko 1.4x Teleplus Pro 300 DGX	19538 C815-Z + 1.4X	22150 N120 Extension Ring 50 II	18802 8.5" Acrylic Dome Port * 18811 140mm Optical Glass Fisheye Port with Removable Shade 18812 230mm Optical Glass Wide Angle Port II
				18802 8.5" Acrylic Dome Port 18810 140mm Optical Glass Fisheye Port 18812 230mm Optical Glass Wide Angle Port II
	Canon EF 15mm f/2.8 Fisheye			18802 8.5" Acrylic Dome Port 18810 140mm Optical Glass Fisheye Port 18812 230mm Optical Glass Wide Angle Port II
	Sigma 15mm F2.8 EX DG Diagonal Fisheye	19546 SC15-F		18802 8.5" Acrylic Dome Port * 18810 140mm Optical Glass Fisheye Port 18812 230mm Optical Glass Wide Angle Port II