



0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 FOR FULL FRAME 14MM EQUIVALENT LENS TO 140° FULL ZOOM-THROUGH

	CAMERA LENS	GEAR	EXTENSION RING	PORT		OPTICAL PERFORMANCE	
WIDE ANGLE APSC	Canon EF-S 10-18mm f/4.5-5.6 IS STM	16340 RC1018 Gear Set		85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 108-75° Converted FOV 128-85°	
	Canon EF-S 10-22mm f/3.5-4.5 IS USM	16303 + 16304 RC1022-Z + RC1022-F	21110 N120 Extension Ring 10	85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 108-63° Converted FOV 128-72°	
			22110 N120 Extension Ring 10 II	85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 108-63° Converted FOV 128-72°	
	Tokina AT-X 11-20mm F2.8 PRO DX	16328 RTC1120 Gear Set	22120 N120 Extension Ring 20 II	85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 100-68° Converted FOV 118-78°	
	Tokina AT-X 116 PRO DX AF 11-16mm f/2.8	16309 + 16310 RSC1116-Z + RSC1116-F	21110 N120 Extension Ring 10	85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 110-81° Converted FOV 118-92°	
			22110 N120 Extension Ring 10 II	85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 110-81° Converted FOV 118-92°	
	WIDE ANGLE FULL FRAME (RED, CANON, PANASONIC, Z-CAM, BLACKMAGIC)	Canon RF 14-35mm f/4L IS USM	16342 CR1435	21110 N120 Extension Ring 10	85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 89-42° Converted FOV 104-48°
				22110 N120 Extension Ring 10 II	85204 N120 WACP - 2	On Full Frame Sensor	Lens FOV 114-63° Converted FOV 140-72°
Canon RF 15-30mm f/4.5-6.3 IS STM		16345 CR1530 Gear Set		85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 84-49° Converted FOV 101-59°	
					On Full Frame Sensor	Lens FOV 110-71° Converted FOV 133-81°	
Canon RF 15-35mm f/2.8L IS USM		16341 CR1535 Gear Set	22135 N120 Extension Ring 35 II	85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 84-42° Converted FOV 98-48°	
					On Full Frame Sensor	Lens FOV 110-63° Converted FOV 133-72°	
Canon EF 16-35mm f/2.8 II USM		16311 + 16312 RC1635II-Z + RC1635II-F	22130 N120 Extension Ring 30 II	85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 84-44° Converted FOV 98-51°	
					On Full Frame Sensor	Lens FOV 107-63° Converted FOV 128-72°	
Canon EF 16-35mm f/2.8 III USM		16325 RC1635III Gear Set	22150 N120 Extension Ring 50 II	85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 84-44° Converted FOV 98-51°	
					On Full Frame Sensor	Lens FOV 107-63° Converted FOV 128-72°	
Canon EF 16-35mm f/4L IS USM		16317 + 16318 RC1635f4-Z + RC1635f4-F	22130 N120 Extension Ring 30 II	85204 N120 WACP - 2	On APS-C Sensor	Lens FOV 84-44° Converted FOV 98-51°	
					On Full Frame Sensor	Lens FOV 107-63° Converted FOV 128-72°	
Canon RF 28-70mm f2L USM		16343 RC2870f2 Gear Set	22140 N120 Extension Ring 40 II	85204 N120 WACP - 2	On Full Frame Sensor	Lens FOV 75-63° Converted FOV 85-72° Zoom Range 28-35mm	

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.

* Recommended port system based on best optical performance



0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 FOR FULL FRAME 14MM EQUIVAMENT LENS TO 140° FULL ZOOM-THROUGH

	CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE
N120 NIKON F-MOUNT	Nikon AF-S NIKKOR 16-35mm f/4G ED VR	19138 N1635-Z	22150 N120 Extension Ring 50 II	* 85204 N120 WACP - 2	Lens FOV 105-63° Converted FOV 128-72°
		19138 + 19142 N1635-Z + N1635-F	22140 + 22131 N120 Extension Ring 40 II + Focus Knob	85204 N120 WACP - 2	Lens FOV 105-63° Converted FOV 128-72°
	Nikon AF-S 17-35mm f/2.8D IF-ED	19130 N1735-Z	22130 N120 Extension Ring 30 II	85204 N120 WACP - 2	Lens FOV 104-63° Converted FOV 123-72°
		19130 + 19159 N1735-Z + N1735-F <i>* a spacer is required for this setup (incl. in package)</i>	22135 + 22151 N120 Extension Ring 35 II + Focus Knob	* 85204 N120 WACP - 2	Lens FOV 104-63° Converted FOV 123-72°
N120 NIKON Z-MOUNT	Nikkor Z 24-70mm f/2.8 S Lens	19157 NZ2470f2.8S-Z	22125 N120 Extension Ring 25 II	85204 N120 WACP - 2	Lens FOV 84-46° Converted FOV 98-56° Zoom Range 24-50mm
	Nikkor Z 14-24mm f/2.8 S	19160 NZ1424-Z	21110 N120 Extension Ring 10	85204 N120 WACP - 2	Lens FOV 114-87° Converted FOV 140-98° <i>* This setup is only compatible with WACP-2 SN:A526311 before</i>
			22110 N120 Extension Ring 10 II	85204 N120 WACP - 2	Lens FOV 114-87° Converted FOV 140-98° <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>
Nikkor Z 14-30mm f/4 S	19156 NZ1430-Z		85204 N120 WACP - 2	Lens FOV 114-72° Converted FOV 140-81°	
N120 CANON EF-MOUNT	Canon EF-S 10-18mm f/4.5-5.6 IS STM	19549 C1018-Z		85204 N120 WACP - 2	Lens FOV 108-75° Converted FOV 128-85°
	Canon EF-S 10-22mm f/3.5-4.5 IS STM	19525 C1022-Z	21110 N120 Extension Ring 10	85204 N120 WACP - 2	Lens FOV 108-63° Converted FOV 128-72° <i>* This setup is only compatible with WACP-2 SN:A526311 before</i>
			22110 N120 Extension Ring 10 II	85204 N120 WACP - 2	Lens FOV 108-63° Converted FOV 128-72° <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>
	Tokina AT-X 11-20mm F2.8 PRO DX	19573 CT1120-Z	22120 N120 Extension Ring 20 II	85204 N120 WACP - 2	Lens FOV 104-72° Converted FOV 123-81°
Tokina AT-X 116 PRO DX AF 11-16mm f/2.8	19530 TC1116-Z	21110 N120 Extension Ring 10	85204 N120 WACP - 2	Lens FOV 110-81° Converted FOV 133-92° <i>* This setup is only compatible with WACP-2 SN:A526311 before</i>	
		22110 N120 Extension Ring 10 II	85204 N120 WACP - 2	Lens FOV 110-81° Converted FOV 133-92° <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>	

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.

* Recommended port system based on best optical performance



0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 FOR FULL FRAME 14MM EQUIVALENT LENS TO 140° FULL ZOOM-THROUGH

	CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE	
N120 CANON EF-MOUNT	WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/2.8 II USM	19527 C1635II-Z	22130 N120 Extension Ring 30 II	* 85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°
		19527 + 19542 C1635II-Z + C1635II-F	22130 + 22131 N120 Extension Ring 30 II + Focus Knob	85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°	
	WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/2.8 III USM	19554 C1635III-Z	22150 N120 Extension Ring 50 II	* 85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°
		19554 + 19555 C1635III-Z + C1635III-F	22150 + 22151 N120 Extension Ring 50 II + Focus Knob	85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°	
	WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/4 IS USM	19548 C1635f4-Z	22130 N120 Extension Ring 30 II	* 85204 N120 WACP - 2	Lens FOV 108-63° Converted FOV 128-72°
		19548 + 19572 C1635f4-Z + WC1635f4-F	22135 + 22151 N120 Extension Ring 35 II + Focus Knob	85204 N120 WACP - 2	Lens FOV 108-63° Converted FOV 128-72°	
N120 CANON RF-MOUNT	WIDE ANGLE FULL FRAME	Canon RF 14-35mm f/4L IS USM	19574 CR1435-Z	21110 N120 Extension Ring 10	85204 N120 WACP - 2	Lens FOV 114-63° Converted FOV 140-72°
		21110 N120 Extension Ring 10 II	85204 N120 WACP - 2	Lens FOV 114-63° Converted FOV 140-72°		
	Canon RF 15-30mm f/4.5-6.3 IS STM	19597 CR1530-Z		85204 N120 WACP - 2	Lens FOV 110-71° Converted FOV 133-81°	
	WIDE ANGLE FULL FRAME	Canon RF 15-35mm f/2.8L IS USM	19569 CR1535-Z	22135 N120 Extension Ring 35 II	85204 N120 WACP - 2	Lens FOV 110-63° Converted FOV 133-72°
		19569 + 19571 CR1535-Z + WCR1535-F	22135 + 22151 N120 Extension Ring 35 II + Focus Knob	* 85204 N120 WACP - 2	Lens FOV 110-63° Converted FOV 133-72°	
	STANDARD ZOOM FULL FRAME	Canon RF 28-70mm f2L USM	19595 CR2870-Z	22140 N120 Extension Ring 40 II	85204 N120 WACP - 2	Lens FOV 75-63° Converted FOV 85-72° Zoom Range 28-35mm
N120 PANASONIC	WIDE ANGLE FULL FRAME	Panasonic Lumix S PRO 16-35mm f/4	19728 PL1635-Z		85204 N120 WACP - 2	Lens FOV 105-63° Converted FOV 128-72°
		Sigma 14-24mm F2.8 DG DN Art	19726 SLE1424-Z	22125 N120 Extension Ring 25 II	85204 N120 WACP - 2	Lens FOV 94-84° Converted FOV 115-98° Zoom Range 20-24mm
N120 FUJIFILM	MACRO MEDIUM FORMAT	Laowa 17mm f/4 GFX Zero-D	19824 + 19825 GL17-A + GL17-F	22135 + 22151 N120 Extension Ring 35 II + Focus Knob	85204 N120 WACP - 2	Lens FOV 114° Converted FOV 140°

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.

* Recommended port system based on best optical performance



0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 FOR FULL FRAME 14MM EQUIVALENT LENS TO 140° FULL ZOOM-THROUGH

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	OPTICAL PERFORMANCE	
N120 FUJIFILM G-MOUNT	WIDE ANGLE MEDIUM FORMAT	Fujifilm GF 23mm F4 R LM WR		22120 N120 Extension Ring 20 II	85204 N120 WACP - 2	Lens FOV 100° Converted FOV 118°	
		Canon EF 16-35mm f/2.8 III USM	TBD CGF1635III-Z	22180 N120 Extension Ring 80 II	85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°	
		Canon EF 16-35mm f/4 IS USM	TBD CGF1635f4-Z	22160 N120 Extension Ring 60 II	85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°	
STANDARD ZOOM FULL FRAME	Sony SEL2470GM FE 24-70mm F2.8 GM	37151 SFE2470GM-Z 37151 + 37152 SFE2470GM-Z + SFE2470GM-F	¹ 37305 N100 to N120 35.5mm Port Adaptor II	22130 N120 Extension Ring 30 II	85204 N120 WACP - 2	Lens FOV 84-34° Converted FOV 98-72° Zoom Range 24-35mm	
	Sony SEL2470Z Vario-Tessar T* FE 24-70mm F4 ZA OSS	37149 SE2470-Z 37149 + 37148 SE2470-Z + SE2470-F	¹ 37305 N100 to N120 35.5mm Port Adaptor II		85204 N120 WACP - 2	Lens FOV 84-34° Converted FOV 98-72° Zoom Range 24-35mm	
	Sigma 24-70mm f/2.8 DG DN Art	37171 SSF2470-Z	¹ 37305 N100 to N120 35.5mm Port Adaptor II	22120 N120 Extension Ring 20 II	85204 N120 WACP - 2	Lens FOV 84-64° Converted FOV 98-74° Zoom Range 24-34mm	
N100 SONY E-MOUNT	WIDE ANGLE FULL FRAME	Sony FE 14mm f/1.8 GM		37306 N100 to N120 25mm Port Adaptor	85204 N120 WACP - 2	Lens FOV 114° Converted FOV 140°	
		Sony SEL1635GM FE 16-35mm F2.8 GM	37155 SFE1635GM-Z 37155 + 37156 SFE1635GM-Z + SFE1635GM-F	¹ 37305 N100 to N120 35.5mm Port Adaptor II	22130 N120 Extension Ring 30 II	85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-77°
		Sony SEL1635Z Vario-Tessar T* FE 16-35mm F4 ZA OSS	37145 + 37146 SE1635-Z + SE1635-F	¹ 37305 N100 to N120 35.5mm Port Adaptor II	21110 N120 Extension Ring 10 22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 85204 N120 WACP - 2	Lens FOV 107-63° Converted FOV 128-77° Lens FOV 107-63° Converted FOV 128-77° <i>* This setup is only compatible with WACP-2 before SN:A526311</i> <i>* This setup is only compatible with WACP-2 SN:A526311 onwards</i>
		Sony FE 24mm f/1.4 GM		¹ 37305 N100 to N120 35.5mm Port Adaptor II		85204 N120 WACP - 2	Lens FOV 84° Converted FOV 98°
		Sigma 14-24mm F2.8 DG DN	19726 SLE1424-Z	¹ 37305 N100 to N120 35.5mm Port Adaptor II	22125 N120 Extension Ring 25 II	85204 N120 WACP - 2	Lens FOV 94-84° Converted FOV 115-98° Zoom Range 20-24mm
		Tamron 17-28mm f/2.8 Di III RXD	37157 STE1728-Z 37157 + 37158 STE1728-Z + STE1728-F	¹ 37305 N100 to N120 35.5mm Port Adaptor II		85204 N120 WACP - 2	Lens FOV 104-75° Converted FOV 123-89°

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.

* Recommended port system based on best optical performance

85204**0.57X WIDE ANGLE CONVERSION PORT WACP-2****Package includes :**

Hard Lens Cap
Rear Port Cap
Spare O-ring 90140
Lubricant
Cleaning Cloth
Carrying Bag

Specification

Dimension (dia x length)	267 x 220 mm
Weight in Air	7.35 kg
Buoyancy in Water	0.27 kg
Body Construction	Hard-anodized aluminum alloy
Lens Construction	4 Elements in 4 Groups
Lens Coating	Anti-reflection Coating on both sides
Lens Mount	N120 Port Mount
Depth Rating	100m
Focal Distance	From front element of lens to infinity
Field of View (Underwater)	140° (ref 14mm equiv.)