



N85 PORT SYSTEM FOR CANON EF-M-MOUNT CAMERA SYSTEM (APS-C Format Lens)

	CAMERA LENS	GEAR	PORT ADAPTOR	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO APS-C	Canon EF-S 60mm f/2.8 Macro USM with Canon EF-M Lens Adapter Kit	36192 CMEF60-F 19521 C60-F	36184 N85 to N120 41.5mm Port Adaptor	36182 Macro Port for Canon EF-EOS M Adaptor	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81302 CMC - 2 81201 SMC - 1	Max. Magnification 1.6X Working Distance 38-120mm Max. Magnification 1.6X Working Distance 28-94mm
				18704 Macro Port 41	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81302 CMC - 2 81201 SMC - 1	Max. Magnification 1.6X Working Distance 38-120mm Max. Magnification 1.6X Working Distance 28-94mm
				SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2 81201 SMC - 1	Max. Magnification 1.6X Working Distance 38-120mm Max. Magnification 1.6X Working Distance 28-94mm	
STANDARD ZOOM APS-C	Canon EF-M 15-45mm f/3.5-6.3 IS STM	36195 CM1545-Z		36135 N85 Macro Port 45	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1 81302 CMC - 2	Max. Magnification 0.8X Working Distance 37-81mm Max. Magnification 0.7X Working Distance 59-150mm
					SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1 81302 CMC - 2	Max. Magnification 0.8X Working Distance 37-81mm Max. Magnification 0.7X Working Distance 59-150mm
					83250 M67 to Bayonet Mount Converter II	¹ 83201 WWL - 1 83202 WWL - 1B 83203 WWL - C	Lens FOV 74-33° Converted FOV 128-57° Zoom Range 18-45mm Lens FOV 74-33° Converted FOV 128-57° Zoom Range 18-45mm Lens FOV 76-33° Converted FOV 117-51° Zoom Range 17-45mm
	Canon EF-M 18-55mm f/3.5-5.6 IS STM	36191 CM1855-Z		36181 4" Acrylic Wide Angle Port	25105 + 81222 M67 Flip Diopter Holder for 36137 + M67 Adapter Ring	81302 CMC - 1	Max. Magnification 0.6X Working Distance 58-127mm
				36131 3.5" Acrylic Wide Angle Port			
				36126 E16 Mancake Port	83250 M67 to Bayonet Mount Converter II	¹ 83201 WWL - 1 83202 WWL - 1B	Lens FOV 63° Converted FOV 109° Lens FOV 63° Converted FOV 109°
Canon EF-M 22mm f/2 STM							
WIDE ANGLE APS-C	Canon EF-M 11-22mm f/4-5.6 IS STM	36194 CM1122-Z	36204 N85 to N120 60mm Port Adaptor	36181 4" Acrylic Wide Angle Port			
				36133 6" Acrylic Wide Angle Port			
				36129 7" Acrylic Dome Port			
				[*] 18809 180mm Optical Glass Wide Angle Port			

1. #36184 & Port Adaptor is incompatible to used on NA-EOSM & NA-EOSM3 housings

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N85 PORT SYSTEM FOR CANON EF-M-MOUNT CAMERA SYSTEM (Full Frame Format Lens with Canon EF-M Lens Adapter Kit)

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
CANON EF-MOUNT	Canon EF 8-15mm f/4L Fisheye USM with Canon EF-M Lens Adapter Kit	36193 CMEF815-Z 19537 C815-Z	36184 N85 to N120 41.5mm Port Adaptor	22130 N120 Extension Ring 30 II	36183 4.33" Acrylic Dome Port for Canon EF 8-15mm f/4L Fisheye USM * 18811 140mm Optical Glass Fisheye Port with Removable Shade			
	Canon EF 100mm f/2.8L Macro IS USM with Canon EF-M Lens Adapter Kit		36204 N85 to N120 60mm Port Adaptor	22130 N120 Extension Ring 30 II	18704 Macro Port 41	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1 81202 SMC - 2 81302 CMC - 2	Max. Magnification 2.0X Working Distance 45-95mm Max. Magnification 3.4X Working Distance 23-39mm Max. Magnification 2.1X Working Distance 53-127mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1 81202 SMC - 2 81302 CMC - 2	Max. Magnification 2.0X Working Distance 45-95mm Max. Magnification 3.4X Working Distance 23-39mm Max. Magnification 2.1X Working Distance 53-127mm
		19523 C100IS-F	36184 N85 to N120 41.5mm Port Adaptor		18703 Macro Port 94	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1 81202 SMC - 2 81302 CMC - 2	Max. Magnification 2.0X Working Distance 45-95mm Max. Magnification 3.4X Working Distance 23-39mm Max. Magnification 2.1X Working Distance 53-127mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1 81202 SMC - 2 81302 CMC - 2	Max. Magnification 2.0X Working Distance 45-95mm Max. Magnification 3.4X Working Distance 23-39mm Max. Magnification 2.1X Working Distance 53-127mm
	Other Canon EF-mount Lenses with Canon EF-M Lens Adapter Kit		36184 N85 to N120 41.5mm Port Adaptor		N120 Canon EF-Mount Port System			

1. #36184 & Port Adaptor is incompatible to used on NA-EOSM & NA-EOSM3 housings

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance