

Instruction Manual for 0.36x Wide Angle Conversion Port with Aluminium Float Collar

PN# 85201

FOREWORD

Thank you for your purchase of a NAUTICAM product.

At NAUTICAM, we pride ourselves in the ability to recognise the requirements of professional as well as amateur underwater photographers and fulfill them through the innovative designs of our products. We strive to achieve a high level of user-friendliness by allowing stress-free installation and easy operation of all important functions of the camera.

Each product is individually inspected and water pressure tested to ensure optimum quality.

Please read this manual carefully before using the product, this will maximise its performance as well as its lifetime.

WARRANTY

All NAUTICAM Housing Products and Viewfinders are warranted against any material and manufacturing defects for two years from the date of purchase for consumer use. NAUTICAM Optical Accessories are warranted against material and manufacturing defects for a period of one year, and HDMI cables carry a four month warranty.

This warranty only applies to products purchased from authorized NAUTICAM dealers and does not extend beyond the original retail purchaser.

To return your product for service, please contact your regional authorized service centre(s). Please note that this warranty only applies when the product is purchased in the territory where the service centre is located.

NAUTICAM does not hold responsibility for damage, of any nature, to any equipment used with and/or placed within our products.

NAUTICAM accepts no liability for any loss of captured images or the inability to capture images even if it is due to the malfunctioning of our products.

Unauthorised modifications and/or repairs of our products will automatically invalidate the warranty.

PACKAGE CONTENTS

- Wide Angle Conversion Port (WACP)
- Aluminium Float Collar (Pre-installed)
- N120 to N100 35mm Port Adaptor (Pre-installed)
- Hard Lens Cap and Rear Cap
- Lens Hood Mounting Ring
- Carrying Bag
- Cleaning Cloth
- Instruction Manual

IDENTIFICATION OF PARTS



REMOVING THE ALUMINIUM FLOAT COLLAR



Remove the six screws around the lens hood.



Push down the float collar from the lens.



Remove the O-Ring from the lens as indicated as well as the six screws.



Replace the spare lens hood mounting ring with the existing one and secure with screws. Align the hood before tightening all the screws.

CARE AND MAINTENANCE

The following procedures are advised to be followed:

- The WACP should be rinsed thoroughly in fresh water after each dive.
- Dry and clean the glass surface of the WACP with the cloth provided.
- Cover the lens with the provided cap when not in use.
- DO NOT use any kind of abrasive solutions to clean the glass surfaces.

SPECIFICATIONS

Lens Construction:	6 elements in 5 groups
Field of view: (Underwater)	130° (Ref. 28mm equiv.)
Focal distance:	0cm to infinity
Dimensions:	Dia130mm x 97mm
Weight: (Air/ Underwater)	w/ collar: approx.. 3.90kg / 0.32kg w/o collar: approx. 3.30kg / 1.50kg
Depth rating:	100m
Mount system:	N120

Please visit <http://www.nauticam.com/support/port-chart/> for the latest WACP compatibility chart.