



N85 PORT SYSTEM FOR CANON EF-M-MOUNT CAMERA SYSTEM (APS-C Format Lens)

| | CAMERA LENS | GEAR | PORT ADAPTOR | PORT | MOUNT CONVERTER | WET LENS | OPTICAL PERFORMANCE | |
|-----------------------|---|-------------------|---|------------------------------------|--|--|--|---|
| MACRO APSC | Canon EF-S 60mm f/2.8 Macro USM with Canon EF-M Lens Adapter Kit | 19521 C60-F | 36184 N85 to N120 41.5mm Port Adaptor | 18704 Macro Port 41 | SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i> | 81302 CMC - 2 | Max. Magnification 1.6X Working Distance 38-120mm | |
| | | | | | SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC | 81201 SMC - 1 | Max. Magnification 1.6X Working Distance 28-94mm | |
| STANDARD ZOOM APSC | Canon EF-M 15-45mm f/3.5-6.3 IS STM | 36195 CM1545-Z | | 36135 N85 Macro Port 45 | SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i> | 81301 CMC - 1 | Max. Magnification 0.8X Working Distance 37-81mm | |
| | | | | | SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC | 81302 CMC - 2 | Max. Magnification 0.7X Working Distance 59-150mm | |
| | | | | | 83250 M67 to Bayonet Mount Converter II | * 83202 WWL - 1B | Lens FOV 74-33° Converted FOV 128-57° Zoom Range 18-45mm | |
| | Canon EF-M 22mm f/2 STM | | | 36126 E16 Mancake Port | 83250 M67 to Bayonet Mount Converter II | 83202 WWL - 1B | Lens FOV 63° Converted FOV 109° | |
| CANON EF-MOUNT | Canon EF 8-15mm f/4L Fisheye USM with Canon EF-M Lens Adapter Kit | 19537 C815-Z | 36184 N85 to N120 41.5mm Port Adaptor | 22130 N120 Extension Ring 30 II | * 18811 140mm Optical Glass Fisheye Port with Removable Shade | | | |
| | Canon EF 100mm f/2.8L Macro IS USM with Canon EF-M Lens Adapter Kit | 19523 C100IS-F | 36204 N85 to N120 60mm Port Adaptor | 22130 N120 Extension Ring 30 II | 18704 Macro Port 41 | SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i> | 81201 SMC - 1 | Max. Magnification 2.0X Working Distance 45-95mm |
| | | | | | | SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC | 81202 SMC - 2 | Max. Magnification 3.4X Working Distance 23-39mm |
| | Other Canon EF-mount Lenses with Canon EF-M Lens Adapter Kit | | 36184 N85 to N120 41.5mm Port Adaptor | | N120 Canon EF-Mount Port System | 81302 CMC - 2 | Max. Magnification 2.1X Working Distance 53-127mm | |

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- * Recommended Nauticam underwater optics based on best underwater optical performance
- * Recommended Port System