



## N100 PORT SYSTEM FOR FUJIFILM X-MOUNT CAMERA SYSTEM ( APS-C Format Lens )

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO APSC	Fujifilm XF 60mm f/2.4 R Macro			<b>37430</b> N100 Extension Ring 30 II	<b>37127</b> N100 Flat Port 32			
	Fujifilm XF 80mm f/2.8 R LM OIS WR Macro	<b>36473</b> X80-F			<b>37125</b> N100 Macro Port 110	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81202</b> SMC - 2	Max. Magnification <b>2.5X</b> Working Distance <b>17-36mm</b>
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC		
	Zeiss Touit 50mm f/2.8M			<b>37430</b> N100 Extension Ring 30 II	<b>37127</b> N100 Flat Port 32	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81301</b> CMC - 1	Max. Magnification <b>1.3X</b> Working Distance <b>17-75mm</b>
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81302</b> CMC - 2	Max. Magnification <b>1.0X</b> Working Distance <b>30-130mm</b>
						<b>83250</b> M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	<b>86201</b> MWL - 1	Lens FOV <b>31°</b> Converted FOV <b>100°</b>
WIDE ANGLE APSC	Fujifilm XF 16-50mm f/2.8-4.8 8 R LM WR	<b>36480</b> XF1650-Z		<b>37408 / 37431</b> N100 Extension Ring 35 / N100 Extension Ring 35 II	<b>85205</b> N100 WACP - C			Lens FOV <b>76-32°</b> Converted FOV <b>132-55°</b> Zoom Range <b>18-50mm</b>
					<b>85206</b> N100/N120 WACP-1B			
					<b>85203</b> N100 WACP-1			
				<b>37433</b> N100 Extension Ring 50 II	<b>37129</b> N100 180mm Optical Glass Wide Angle Port			
	Fujifilm XF 10-24mm f/4 R OIS WR	<b>36479</b> X1024WR-Z		<b>37433</b> N100 Extension Ring 50 II	* <b>37129</b> N100 180mm Optical Glass Wide Angle Port			
			<b>37304</b> N100 to N120 55mm Port Adaptor <i>* This setup is only compatible with 37304 SN:A411796 onwards, older version 37304 can be upgraded using lock mechanism 95851</i>		<b>18809</b> 180mm Optical Glass Wide Angle Port			
	Fujifilm XF 18mm f/2 R				<b>36472</b> N100 Flat Port 13	<b>83250</b> M67 to Bayonet Mount Converter II	<b>83202</b> WWL - 1B	Lens FOV <b>76.5°</b> Converted FOV <b>132°</b>
	Fujifilm XF 23mm f/2 R				<b>37127</b> N100 Flat Port 32	<b>83250</b> M67 to Bayonet Mount Converter II	<b>83202</b> WWL - 1B	Lens FOV <b>63.4°</b> Converted FOV <b>110°</b>

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- \* Recommended Nauticam underwater optics based on best underwater optical performance
- \* Recommended Port System

Last Updated : 2026-03-27

\* This port chart is subject to updating as new information becomes available